



PRODUCT DATA SHEET

Frameseal bead with shadow gap, mesh
6 mm
Item no. 37806



Status: 31.07.2026 | 23:49



Designation	Frameseal bead with shadow gap, mesh 6 mm
Description	The self-adhesive PROTEKTOR PVC frame seal bead with sewn-on alkali-resistant glass fibre mesh, shadow gap and tear-off adhesive tab for foil covering is suitable for creating visually and technically flawless connections between windows, doors and other components and plaster and ETICS systems. With perforated plastering leg and sewn-on mesh for high-strength plaster integration. The foam tape is self-adhesive and closed-cell. Profile width 6 mm for ETICS systems and plaster from 6 mm.
Product area	Thermal insulation
Product category	Soffit profiles
Plaster thickness	6 mm
Product width	6 mm
Air and component temperature	+5° bis +40°C
Grammage	160 g/m²
	3 mm
	5 mm
Mesh size	4 x 4 mm
Appearance	Self-adhesive, closed-cell foam tape.
Underground	Adhesive areas must be flat, dry (note possible condensation), free of frost, dust and grease, and firm and stable. An adhesive test will determine whether the substrate is suitable for adhesion or whether special measures (e.g. cleaning) are required.
Treatment	For underground with lightness value greater than 7.
Overplastering Ability	Single-sided mesh overlap of 10 cm from end of bar.
Storage	Store profiles in a dry, frost-free place, lying flat and horizontally in the box. Do not store or transport profiles in a twisted or bent position. Protect boxes and/or profiles from excessive heat and direct sunlight. To remove the profiles, open the box along its entire length.
Impermeability to driving rain	bis 1050 Pa
Annotation	Single-sided mesh overlap of 10 cm from end of bar.
Movement according to ÖNORM B6400/ÖAP VAR VII	Klasse IC

PRODUCT DATA SHEET

Frameseal bead with shadow gap, mesh

6 mm

Item no. 37806



Movement according to VDPM leaflet/SAF guideline	Klasse C
product line	BasicLine
Test report	Geprüfte Luft-, Wind- und Schlagregendichtheit, geprüfte Bewegungsaufnahme. Die jeweils aktuellen Prüfberichte stehen auf www.protektor.de zum Download bereit.
Leaflet	* Leaflet * Fiche technique Formation de détails avec des profilés et des bandes d'étanchéité de joints pour l'enduit extérieur et l'ETICS, éditeur Verband für Dämmsysteme, Putz und Mörtel e.V. (VDPM). * Instruction sheet for association guidelines on connections to windows and shutters for plaster, thermal insulation composite systems and dry construction, published by the Association of Plasterers for Interiors and Facades.
Shadow gap	3 mm
Airtightness	bis 600 Pa
Customs tariff number	39269097
Opened label	Purchase only possible as full packaging units.

Item number	Length (cm)	Plaster thickness	Material	Colour	Packaging unit
111389	260.00	6 mm	Rigid PVC with glass fibre mesh	10 - white	50 PCS / 13 BOX

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!